

SIEMENS

Data sheet for SIMOTICS 1LE0323 Low-Voltage Motor

MLFB-Ordering data: 1LE0023-1EB43-4AA4



Motor type:

Client order no.:

Order no.:

Offer no.:

Remarks:

U [V]	Δ/Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N I ₁ /I _N	M _A /M _N T ₁ /T _N	M _K /M _N T _B /T _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
400	Δ	50	22	- / -	41.0	1470	143	93.0	93.7	93.6	0.83	- / -	- / -	7.8	2.6	3.6	IE3
690	Y	50	22	- / -	24.0	1470	143	93.0	93.7	93.6	0.83	- / -	- / -	7.8	2.6	3.6	IE3
IM B3			FS 180L		192 kg	IP55		IEC/EN 60034			IEC, DIN, ISO, VDE, EN						

Mechanical data

Sound pressure level 50Hz/60Hz	63 dB(A)	- / -
Moment of inertia	0.146 kgm ²	
Bearing DE NDE	6210 Z C3 6210 Z C3	
Bearing lifetime	- / -	
Lubricants	- / -	
Regreasing device	No	
Grease nipple	- / -	
Type of bearing	floating bearing DE and NDE	
Condensate drainage holes	No	
External earthing terminal	No	
Vibration class	A	
Insulation	155(F)	
Duty type	S1	
Direction of rotation	bidirectional	
Frame material	cast iron	
Data of anti condensation heating	- / -	
Coating	Yes	
Color	RAL7030	
Motor protection	- / -	
Method of cooling	IC411 - self ventilated, surface cooled	

Terminal box

Terminal box position	top
Material of terminal box	cast iron
Type of terminal box	- / -
Gland size / Plug size	M40x1.5/M40x1.5
Cable diameter	22-32
Max. auxiliary terminals	- / -
Auxiliary cable entry	- / -
Main terminal thread	6xM5

Special design

Environmental conditions

Ambient temperature	-20 °C ~ +40 °C
Altitude above sea level	1000 m

Unrestricted

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

Page 1/1

Version: 2020.07