

LUBRICATION SOLUTIONS

METALWORKING FLUIDS



ROLLER LUBRICATION

REDUCE

COSTS

**IMPROVE
PRODUCTIVITY**

ROLLER LINE

- Optimal spreading and control of the lubricant
- For any kind of lubricant
- No mist
- Very significant oil consumption reduction
- Comply with the most demanding HSE requirements
- High reliability
- Very low maintenance costs
- Different widths available

MOLYDAL since 1958

Leader in the production of metalworking fluids, MOLYDAL offers a complete range of products and solutions complying with users' technical and environmental requirements:

- Vanishing fluids
- Neat oils
- Minimal quantity lubrication oils
- Soluble oils

To meet each customer's needs, MOLYDAL has developed:

- VOC-free eco-responsible products; MOLYDAL's R&D laboratory is particularly involved in the design of new vegetable-based products.
- High-performance products for the cutting operations.
- Drawing and profiling sectors.
- Lubrication systems with rollers as well as minimal quantity lubrication systems.

A local advisory team is at users' disposal, giving them guidance, solutions and customised recommendations

PRODUCTS LIST

| | |
|--------------------|---------|
| DES 5000 | 10 |
| Machining fluids | 9 |
| Evaporables fluids | 4 |
| H 125 AL | 6 |
| H 128 | 6 |
| H 526 | 6 |
| H 528 | 6, 7 |
| H 570 | 6, 7 |
| HCB 300 | 6, 8 |
| HCB 400 | 6, 9 |
| Neat oils | 6 |
| Soluble oils | 10 |
| HVG | 8 |
| LUBA 21 | 6, 7 |
| LUBA 40 | 6, 7 |
| LUBA 50 | 6, 8, 9 |
| LUBA 200 | 6, 8 |
| LUBA 216 AL | 6, 8 |
| LUBA 251 | 6, 7 |
| MY 0 | 4 |
| MY 1 | 4 |
| MY 13 | 4 |
| MYC 60 | 4, 5 |
| MYC 129 | 4 |
| MYC 170 | 5 |
| MYE 605 AL | 4, 5 |
| MYE 607 AL | 4, 5 |
| MYE 610 | 4, 5 |
| MYE 615 AL | 4, 5 |
| SOLCUT 700 BS | 10 |
| SOLESTER 77 | 10 |
| SOLESTER 530/540 | 10 |
| STAREX | 9 |
| TEREBOR | 9 |
| VG CUT 77 | 9 |



EVAPORABLES FLUIDS

| | MY 0 | MY 1 | MY 13 | MYC 129 | MYC 170 | MYC 60 | MYE 605 AL | MYE 607 AL | MYE 610 | MYE 615 AL |
|------------------------|--------|--------|-------|---------|---------|--------|------------|------------|---------|------------|
| Flash point | 41°C | 62°C | 36°C | 116°C | 62°C | 103°C | 41°C | 62°C | 62°C | 62°C |
| V.O.C. content | Yes | Yes | Yes | No | Yes | No | Yes | Yes | Yes | Yes |
| Viscosity @ 20°C (Cst) | 1,30 | 1,30 | 2,50 | 3,00 | 2,50 | | 2,00 | 2,00 | 2,00 | 3,00 |
| CLP classified | Yes | Yes | Yes | Yes | Yes | No | Yes | Yes | Yes | Yes |
| NSF approved | NSF H1 | NSF H1 | No | No | No | No | FDA | FDA | No | NSF H1 |
| Light duty | ● | ● | | | | | ● | ● | ● | |
| Medium duty | | | ● | ● | ● | | | ● | | |
| Heavy duty | | | ● | | ● | ● | | | | ● |
| Profiling | ● | ● | | | | | | | ● | |



MY 0

DESCRIPTION

Fast-evaporating colourless fluid with a hydrocarbon base. Approved by NSF on the requirements of the FDA, in category H1, registration 129621. For cold deforming of all metals of slight thickness. Makes it possible to avoid subsequent degreasing operations. Can be bonded, welded, and painted.

USE

For all cutting, stamping, profiling, folding, cambering, and light stamping operations on all types of metals (ferrous metals, stainless and coated steels, cuprous, bronze, brass, aluminium, and its alloys) of slight thickness.



MY 1

DESCRIPTION

Evaporable colourless fluid with a hydrocarbon base. Approved by NSF on the requirements of the FDA, in category H1, registration 128921. For cold deforming of all metals of slight thickness. Makes it possible to avoid subsequent degreasing operations. Can be bonded, welded, and painted.

USE

For all cutting, stamping, profiling, folding, cambering, and light stamping operations on all types of metals (ferrous metals, stainless and coated steels, cuprous, bronze, brass, aluminium, and its alloys) of slight thickness.



MY 13

DESCRIPTION

Fast-evaporating fluid made up of hydrocarbons reinforced with extreme-pressure, anti-wear additives as well as smoothening agents. Guaranteed chlorine-free and free of animal fat. Imperceptible dry film, practically free of sticky residue and white traces. Can be bonded, welded, and painted.

USE

For deforming difficult parts. For all cutting, stamping, profiling, folding, cambering, and light stamping operations on all types of metals (ferrous metals, stainless and coated steels, cuprous, bronze, brass, aluminium, and its alloys) of medium to large thickness.



MYC 170

DESCRIPTION

Colourless liquid product made up of hydrocarbons reinforced with extreme-pressure, anti-wear additives as well as smoothening agents. Characterised by a near absence of sticky residues, white traces after evaporation. Does not clog spraying systems or nozzles.

USE

For all operations of: cutting; stamping; folding; cambering; rolling; profiling. On all metals. Ready for use and does not require any preparation or any control of the concentration. Can be applied indifferently: to felt; to the roller; as drip feed; by spraying at a rate of 1 to 4 grammes per m2 according to the operation.



MYC 60

DESCRIPTION

VOC-free and high flash point vanishing oil. Its viscosity prevents from hazard phrase H304. Very low friction coefficient. MYC60 is formulated with aliphatic hydrocarbons and onctuousity additives. Thanks to its limited evaporation speed and its outstanding wetting property, it enables to decrease oil consumption.

USE

Cutting, punching, profiling any kind of metals.



MYE 605 AL

DESCRIPTION

Evaporable fluid for incidental contact with foodstuffs made up of hydrocarbons reinforced with extreme-pressure and anti-wear additives as well as smoothening agents. Comprised only of raw materials approved by the FDA. Guaranteed chlorine-free, sulphur-free and free of animal fat. Imperceptible dry film, practically free of sticky residue and white traces. Can be bonded, welded, and painted.

USE

For manufacturing parts intended for food industries. For cold deforming of all metals. For all cutting, stamping, profiling, folding, cambering, and stamping operations on all types of metals (ferrous metals, stainless and coated steels, cuprous, bronze, brass, aluminium, and its alloys).



MYE 607 AL

DESCRIPTION

Evaporable fluid made up of hydrocarbons reinforced with extreme-pressure, anti-wear additives as well as smoothening agents. Comprised only of raw materials approved by the FDA. Guaranteed chlorine-free, sulphur-free and free of animal fat. Imperceptible dry film, practically free of sticky residue and white traces. Can be bonded, and welded.

USE

For manufacturing parts intended for food industries. For cold deforming of all metals. For all cutting, stamping, profiling, folding, cambering, and stamping operations on all types of metals (ferrous metals, stainless and coated steels, cuprous, bronze, brass, aluminium, and its alloys).



MYE 610

DESCRIPTION

Colourless evaporable fluid made up of hydrocarbons reinforced with extreme-pressure, anti-wear additives as well as smoothening agents. Guaranteed chlorine-free, sulphur-free and free of animal fat. Imperceptible dry film, practically free of sticky residue and white traces. Can be bonded, welded, and painted.

USE

For cold deforming of all metals of slight thickness. For all profiling, cutting, stamping, folding, cambering, and stamping operations on all types of metals (ferrous metals, stainless and coated steels, cuprous, bronze, brass, aluminium, and its alloys).



MYE 615 AL

DESCRIPTION

Evaporable fluid made up of hydrocarbons reinforced with extreme-pressure, anti-wear additives as well as smoothening agents. Approved by NSF on the requirements of the FDA, in category H1, registration 130185. Guaranteed chlorine-free, sulphur-free and free of animal fat. Slightly oily film, practically free of sticky residue and white traces. Can be bonded, and welded.

USE

For cold deforming of all metals. For all cutting, stamping, profiling, folding, cambering, and stamping operations on all types of metals (ferrous metals, stainless and coated steels, cuprous, bronze, brass, aluminium, and its alloys).

| | H 125 AL | H 128 | H 528 | H 526 | H 570 | LUBA 21 | LUBA 251 | LUBA 40 | LUBA 50 | LUBA 200 | LUBA 216 AL | H VG | HCB 300 | HCB 400 |
|--------------------------------------|-----------|-------|--------|--------|--------|----------------|----------------|-------------|-------------|----------|-------------|-------------|----------------|----------------|
| Viscosity @ 40°C (Cst) | 22 | 25 | 28 | 110 | 170 | 4 - 6 | 8 -10 | 8 | 50 | 200 | 42 – 50 | 40 | 42 | 29 |
| Aspect, Colour | Colorless | Amber | Yellow | Amber | Amber | Co- lorless | Co- lorless | Yel- low | Yel- low | Amber | Yellow | Yel- low | Pale yellow | Pale yellow |
| 4 balls test : welding (kg) | 160 | 250 | 720 | 800 | 800 | 150 | 150 | 600 | > 800 | 800 | 160 | 160 | 250 | 250 |
| 4 balls test : wear (mm) | / | 0,8 | < 0,70 | < 0,70 | < 0,70 | 0,70 | 0,6 | < 0,6 | < 0,9 | < 1 | / | / | < 0,5 | < 0,5 |
| CLP classified | No | Yes | No | No | No | No | No | No | No | No | No | No | Yes | Yes |
| NSF approved | Yes | No | No | No | No | No | No | No | No | No | Yes | Yes | No | No |
| Ecofriendly | No | No | No | No | No | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Light duty | ● | ● | ● | | | ● | ● | ● | | | ● | ● | | |
| Medium duty | | ● | ● | | | | ● | ● | ● | | | | | |
| Heavy duty | | | | ● | ● | | | | ● | ● | | | | |
| Light cutting and stamping | ● | ● | ● | | | ● | ● | ● | | | ● | ● | | |
| Deep-drawing and heavy stamping | | | | ● | ● | | | | ● | ● | | | | |
| Drilling, threading, tappind, sawing | | ● | ● | | | | | | ● | | | | ● | ● |



H 125 AL

NEAT OIL FOR INCIDENTAL CONTACT WITH FOODSTUFFS

DESCRIPTION

High-viscosity mineral oil for direct and indirect contact with foodstuffs. Approved by NSF on the requirements of the FDA, in category H1 and 3H, registration 137920. Silicone-free. Can be used on all metals and compatible with most elastomers and plastic materials. Colour: Colourless.

USE

For cutting or light stamping operations for the manufacture of parts intended for the food processing industries. For operations of cutting, deep drawing, and folding on all metals (covers, tin cans, etc.) to be used with drip feed, manual roller, a spray without air or with low-pressure air.

| PACKING | REF |
|------------|----------|
| 60 L KEG | H125AL60 |
| 215 L DRUM | H125ALFT |



H 128

NON-CHLORINATED NEAT OIL (SPECIAL CUPROUS)

DESCRIPTION

Low-viscosity, chlorine-free cutting oil. Colour: amber.

USE

For cutting and light stamping operations on all metals. Can be used for machining operations on ferrous or non-ferrous metals (scalping, sawing, drilling and boring). Can be used with drip feed, manual roller, roller machine, a spray without air or with low-pressure air.

| PACKING | REF |
|------------|--------|
| 200 L DRUM | H128FT |



H 528

NON-CHLORINATED NEAT OIL

DESCRIPTION

Mineral based cutting fluid. Free from chlorine. Made with renewable resources improving antifriction power.

USE

Low viscosity oil for sawing any kind of metals of low thickness.

| PACKING | REF |
|---------------|--------|
| 200 L DRUM | H528FT |
| 20 L JERRYCAN | H52820 |



H 526

NON-CHLORINATED NEAT OIL

DESCRIPTION

Mineral based cutting fluid. Free from chlorine. Made with renewable resources improving antifriction power.

USE

Medium viscosity fluid for any kind of stamping and cutting operations on any materials.



H 570

CHLORINE-FREE METALWORKING NEAT OIL

DESCRIPTION

Chlorine-free mineral based cutting fluid. Superior antifriction properties thanks to renewable materials addition.

USE

High viscosity oil for deep drawing and heavy stamping operations.



LUBA 21

ECOFRIENDLY LUBRICANT FOR PROFILING AND LIGHT CUTTING OPERATIONS

DESCRIPTION

Cold forming chlorine-free fluid. Designed to replace solvanted oils and mineral based fluids. Made from vegetal synthetic esters, it possesses an outstanding wetting power allowing better parts finishings and longer tools lifetime.

USE

Specifically designed for cutting, bending, punching, stamping operations. Highly suitable for sawing, drilling and threading operations. Recommended for light stamping.



LUBA 251

ECOFRIENDLY LUBRICANT FOR CUTTING AND LIGHT STAMPING OPERATIONS

DESCRIPTION

Cold forming chlorine-free fluid. Designed to replace solvanted oils and mineral based fluids. Made from vegetal synthetic esters, it possesses an outstanding wetting power allowing better parts finishings and longer tools lifetime.

USE

LUBA251 can be used on any material: aluminum, steel, stainless steel. It is suitable for any coldforming operations. can be applied by rollers, droplets, MQL systems.



LUBA 40

ECOFRIENDLY EXTREME PRESSURE LUBRICANT FOR CUTTING AND STAMPING OPERATIONS

DESCRIPTION

Cold forming chlorine-free fluid. Designed to replace solvanted oils and mineral based fluids. Made from vegetal synthetic esters, it possesses an outstanding wetting power allowing better parts finishings and longer tools lifetime.

USE

Specifically designed for severe stamping operations for any material: steel, stainless steel, aluminum and alloys. Suitable for threading, machining operations.



LUBA 50

ECOFRIENDLY EXTREME PRESSURE LUBRICANT FOR DEEP-DRAWING OPERATIONS

DESCRIPTION

Cold forming chlorine-free fluid. Designed to replace solvanted oils and mineral based fluids. Made from vegetal synthetic esters, it possesses an outstanding wetting power allowing better parts finishings and longer tools lifetime.

USE

For deep-drawing operations on any materials: steel, stainless steel, aluminum, copper and their alloys (on copper, rinse off immediately). Suitable for threading and drilling operations on stainless steel and inconel.

| PACKING | | REF |
|---------|----------|----------|
| 20 L | JERRYCAN | LUBA5020 |
| 200 L | DRUM | LUBA50FT |
| 125 ML | BOTTLE | LUBA50FL |



LUBA 200

EXTREME PRESSURE ECO-FRIENDLY LUBRICANT FOR DEEP-DRAWING OPERATIONS

DESCRIPTION

Cold forming synthetic vegetal ester based fluid. Designed to replaced chlorintated or high viscosisty mineral oils. Its wetting properties enables to improve parts finishings and tools lifetime.

USE

for deep-drawing operations on any material (even copper and alloys). can also be used for threading, drilling.

| PACKING | | REF |
|---------|----------|-------------|
| 200 L | DRUM | LUBA200FT_ |
| 20 L | JERRYCAN | LUBA200_20_ |



LUBA 216 AL

EXTREME PRESSURE ECO-FRIENDLY LUBRICANT FOR CUTTING - STAMPING - ACCIDENTAL CONTACT WITH FOOD

DESCRIPTION

Fluid exclusively made from renewable ressources. V.O.C. Free. Odourless and non irritating.without risk of explosion, and without safety labelling. Silicone free. MOSH-MOAH and POSH free lubricant.

USE

For cutting, stamping and bending operation on all materials except annealed stainless steel. Highly recommended for cold forming operations in the agrofood industry, metalpackaging etc...

| PACKING | | REF |
|---------|----------|-------------|
| 20 L | JERRYCAN | LUBA216AL20 |
| 200 L | DRUM | LUBA216ALFT |



HVG

VEGETABLE OIL FOR DIRECT CONTACT

DESCRIPTION

Clean and general-purpose lubricant recommended for lubrication operation, cutting or light stamping in all fields of activities in the food industry. Free from silicone, allergens and GMO. Approved for the food industry - certified by the National Sanitation Foundation (NSF), which is based on the Food and Drug Administration's (FDA) class 3H, H1 requirements (Registration number 162091). This product is also acceptable for use as a release agent on grills, ovens, loaf pans, boning benches, chopping boards or other hard surfaces in contact with food. MOSH-MOAH and POSH free lubricant.

USE

For all stamping, drop-stamping, bending, medium to heavy thickness on all metals except hardened or tempered stainless steels. Product ideally recommended for all cold forming operations on metals, tin, packing, etc...

| PACKING | | REF |
|---------|------|--------|
| 200 L | DRUM | HVGFT |
| 20 L | CAN | HVG20_ |



HCB 300

NEAT OIL FOR MICRO-SPRAYING

DESCRIPTION

Low-viscosity synthetic cutting fluid, formulated on an ester base, reinforced with an extreme pressure and anti-wear additive. For machining operations using micro-spraying, reducing the amount of lubricant and increasing cutting speeds.

USE

For drilling, tapping, sawing, milling, etc. operations... Also used for cross-cutting aluminium profiles.

| PACKING | | REF |
|---------|----------|----------|
| 20 L | JERRYCAN | HCB30020 |
| 200 L | DRUM | HCB300FT |



HCB 400

NEAT OIL FOR MICRO-SPRAYING

DESCRIPTION

Low-viscosity synthetic cutting fluid, formulated on an ester base, reinforced with an extreme pressure and anti-wear additive. For machining operations using micro-spraying, reducing the amount of lubricant and increasing cutting speeds.

USE

For drilling, tapping, sawing, milling, etc. operations... Also used for cross-cutting aluminium profiles.

Machining fluids



STAREX

EXTREME PRESSURE CUTTING OIL

DESCRIPTION

Special extreme pressure oil for accurate and localised application. Can be used on all grades of steel and on light and cuprous alloys.

USE

For various machining, drilling and tapping operations, by manual application. We recommend degreasing quickly to prevent superficial staining if visual appearance is important.



VG CUT 77

ECOFRIENDLY AQUEOUS DRILLING/TAPPING LUBRICANT

DESCRIPTION

Ready-to-use aqueous fluid without V.O.C. non-flammable, V.O.C free Vegetable polymer-based. Odourless. No smoke emissions. Compatible with all types of metal, including copper and its alloys. Easy to degrease.

USE

For drilling and tapping.



TEREBOR

TAPPING, DRILLING AND MACHINING FLUID

DESCRIPTION

Low-viscosity lubricant for drilling, tapping, and machining. Blue colour.

USE

For tapping high resistance extra hard steel, refractory steels and stainless steel. Chip removal on small diameters, blind holes and metals with low machinability, on automatic or semi-automatic machines.



LUBA 50

ECOFRIENDLY, TAPPING, DRILLING AND MACHINING FLUID

DESCRIPTION

Designed to replace chlorinated mineral oils for threading and drilling, tapping operations. Made from vegetal esters, it possesses and outstanding wetting power. It increases tools lifetime and improves parts finishings.

USE

Can be used on any materials: stainless steel, steel, aluminum, copper etc.

SOLUBLE OILS

| | SOLCUT 700 BS | SOLESTER 530 | SOLESTER 540 | SOLESTER 77 |
|-----------------------------------|------------------|------------------|------------------|--------------|
| Viscosity @ 40°C | 27 | 20 | 80 | 2 |
| Basis oil | Mineral | Ester | Ester | Ester |
| Dilution | 5 to 10 % | 1 to 10 % | 1 to 10 % | Ready to use |
| Emulsion stability | Stable up to 15% | Stable up to 25% | Stable up to 25% | Total |
| Refractometer reading coefficient | 1,1 | 1,2 | 1 | / |
| Ecofriendly | No | Yes | Yes | Yes |
| Light duty | ● | ● | ● | |
| Medium duty | | ● | ● | |
| Heavy duty | | | ● | |
| Profiling | ● | ● | ● | ● |



SOLCUT 700 BS

CHLORINE-FREE MULTI-PURPOSE SOLUBLE OIL

DESCRIPTION

Milky emulsion with good stability. It can be used with ordinary water. Guaranteed bore-free as well as being free of chlorine derivatives, secondary amines, and formaldehyde. Can be used on all types of metals (ferrous, cuprous, and aluminium).

USE

Effective protection against corrosion for parts, tools, and machines. For all chip-removal operations. Machining, thread-cutting, tapping, drilling, turning, and milling. from 5% to more than 10% in water, depending on difficulties and the extent of deformations.



SOLESTER 530 / 540

MICROEMULSION FOR ANY MATERIALS (EVEN COPPER AND ITS ALLOYS)

DESCRIPTION

Synthetic emulsion, from a blend of green chemicals and polyesters. Harmless to operators: no mineral oil, no VOC, no chlorine not CFC or formaldehyde. No hazardous labels or phrases.

USE

From 2% to 8% for any machining operation. 1% to 2% for grinding.



SOLESTER 77

WATER-BASED PROFILING FLUID

DESCRIPTION

Vegetable polymer based ready-to-use aqueous fluid, V.O.C free, non-flammable. Non hazardous (very safe for operators). Compatible with all types of metal, including copper and its alloys.

USE

Zinc-plated electro-galvanised steel profiling. Cutting and stamping without drawing out Stainless-steel rolling (manufacturing chimney sheaths). Manufacture of profiles of the gypsum panel type. Manufacture of vineyard posts



DES 5000

EMULSION TREATMENT

DESCRIPTION

Biocide-free cleaner. DES 5000 is not an instantly-acting treatment but brings stability to the emulsion on the long-term. VOC-free and contains no formaldehyde.

USE


DES 5000 is used to clean machining circuits. It helps maintaining the emulsion stability in order to increase the emulsion lifetime. The treatment must be made while operating.

MINIMUM QUANTITY LUBRICATION

Microlubrication consists in dosing and delivering a very small amount of lubricant thanks to a nozzle and a micropump.



The liquid flows from the reservoir into a piston pump. This pushes an exact quantity of the lubricant into the internal feed tube. Separately supplied compressed air splits the medium at the nozzle tip and sprays it. External MQL in all metal-cutting operations. Pinpoint or small area lubrication in chipless forming operations. Application of mould release and anti-corrosion agents or other spray-on substances.



ADVANTAGES:

- Workstation cleanliness
- Tools lifetime
- Parts finishings improvement
- Very low consumption



A French company on a human scale engaged in certification and approval processes, MOLYDAL continues to consolidate its presence in Europe and pursue its development worldwide. The company's know-how has enabled it to offer a complete range of products and equipment intended for all business sectors (Metalwork, food industries, sugar industries, iron industry, granulation industry, plastic injection, automotive, energy, etc.), where certain approvals are sometimes required (PMUC, NSF, etc.).

THE MOLYDAL VALUES

- Quality policy with a product range designed in compliance with all regulations in force.
- Environmental policy with an eco-responsible product range, with performance equal or superior to current oil solutions.
- Innovation policy with the formulation and testing of the products of tomorrow by the integrated R&D laboratory.


THE MOLYDAL OBJECTIVES

- Pursue the development of the products and materials range to help industries to optimize the profitability of their processes.
- Pursue the company's partnership with various industries to optimize its range of products adapted to the specific features and/or the constraints of manufacturing processes.

THE MOLYDAL SERVICES

- Technical solutions to specific industrial problems: customised recommendations and analysis.
- Responsive teams nearby for a personalised local service.
- The resumption of our chlorinated and non-chlorinated used products (field in keeping with waste recovery).

YOUR REPRESENTATIVE



We are ISO 9001: 2015 approved for quality.



Z.A.E.T. 221, rue Paul Langevin - 60740 Saint-Maximin - FRANCE

Tél : +33 (0)3 44 61 76 76 Fax : +33 (0)3 44 25 17 78

www.molydal.com Contact : molydal@molydal.com